

PROTECTIVE MASK FFP2

52-000-0061A (C0810 Model)

Disposable protective folded mask.

High filtration efficiency particulate protection mask.

Low breathing resistance with high filtration efficiency.

Adjustable nose bridge.



Composition

Mask body Outer layer 1: 100% Polypropylene non-woven fabric, white 45 gsm
Middle layers 2&3: 100% Polypropylene melt blown fabric, white 25 gsm
Middle layer 4: 100% Polypropylene spunbonded, hot air cotton, white 50 gsm
Inner layer 5: 100% Polypropylene non-woven fabric, white 25 gsm

Ear band 30% Spandex, 70% Nylon

Nose bridge Aluminium Silver alloy

Specification

Design: Ears wearing 195 x 5 mm
Outside adjustable bridge 90 x 5 mm

Storage: Temperature between 20°C - 38°C
Humidity < 80%

Shelf-life: 3 years from date of manufacture
In a well ventilated, dark and dry environment

Quantity: 20 pcs/pack – 50 boxes/carton

MOQ: 1 000 pieces

Made in: China



Compliance

Conformity: CE certified
Meets Requirement in Annex II of Regulation (EU) 2016/425 [Cat.III PPE]

Standard: EN149:2001+A1:2009

Class: EN 149:2001+A1:2009: FFP2 NR
Particle filtering half mask limited to single shift use

Certificate number FI20/966585 and CN20/42312
Authorised by SGS FIMKO OY, Notified Body 0598.
Address: Takomotie, 8 FI-00380 Helsinki, FINLAND.